

Ralph E. Jocke Palent & Trademark Law

RECEIVED CENTRAL FAX CENTER NOV 0 2 2004

## FACSIMILE TRANSMISSION COVER SHEET

TRANSMITTING:

6 PAGES (INCLUDING THIS PAGE)

NAME:

Suzanne Dino Barrett

Art Unit 3676
Commissioner for Patents

U.S. Patent and Trademark Office

FAX NUMBER:

(703) 305-7687

DATE:

November 2, 2004

SENDER:

Ralph E. Jocke, Esq.

FAX NUMBER:

112111011222

(330) 722-6446

COMMENTS:

Informal/Draft Communication. Proposed amendment for purposes of

an interview regarding Application No. 10/621,424. Please refer to the

following.

PHONE NUMBER: (330) 721-0000

If you do not receive all pages, contact the sender IMMEDIATELY at the number listed below.

The information contained in this facsimile message is confidential and intended only for the use of the individual or entity named above. If the reader of this message is not the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited and will be considered at a tortious interference in our confidential business relationships. If you have received this communication in error, please immediately notify us by telephone and return the original message to us at the address below via the U.S. Postal Service. Thank you.

330 • 721 • 0000 MEDINA 330 • 225 • 1669 CLEVELAND 330 • 722 • 6446 FACSIMILE rej@walkerandjockc.com E-MAIL

231 South

Broadway.

Medina.

Ohio

U.S.A. 44256-2601

RECEIVED CENTRAL FAX CENTER NOV 0 2 2004

Mail Stop AF Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Re:

Attn: Art Unit 3676

Patent Examiner Suzanne Dino Barrett

Application Serial No.:

10/621,424 1747

Confirmation No.:
Applicants:

Richard W. McCracken, et al.

Title:

Locking Bolt Work Apparatus For ATM

Docket No.:

D-1223R

Sir:

Please find attached a Request for an interview with the Examiner and a Draft Proposed Amendment for purposes of the interview. Applicants reserve the right to file a formal Response to the Office Action dated August 17, 2004.

Very truly yours,

Ralph E. Jocke Reg. No. 31,029

## Request for Interview

Applicants request an interview to discuss the attached proposed amendment to claims 30, 31, and 34. The proposed amendment is in response to the Office Action dated August 17, 2004. Applicants respectfully submit that entry of the proposed amendment would place the application in condition for allowance.

## Proposed Amendments

30. (currently amended) The apparatus according to claim 1 further Apparatus comprising:

a locking bolt work apparatus enabling selective securing of a door, including:

an clongated locking bolt movably mounted relative to a door, the locking bolt movable between extended and retracted positions;

a drive cam rotatably mounted in supporting connection with the door adjacent to a first end portion of the locking bolt;

an idler cam rotatably mounted in supporting connection with the coor adjacent to a second end portion of the locking bolt;

a cam link operatively extending between the drive cam and the idler cam;

a first bolt link operatively extending between the drive cam and the locking bolt;

a second bolt link operatively extending between the idler cam and the locking

wherein rotational movement of the drive cam between a first position and a second position moves the locking bolt between the extended position and the retracted position, respectively;

a door handle assembly, including:

a sleeve,

wherein the sleeve is attached to the door adjacent a door hole, wherein the sleeve includes a tapered inner surface,

a handle shaft,

wherein the handle shaft includes a tapered outer surface,

a handle lever,

wherein the inner surface is operative to engage the outer surface to prevent removal of the handle shaft through the door hole in a direction away from the handle lever.

31. (currently amended) Apparatus comprising:

a door handle assembly, including:

a sleeve.

wherein the sleeve is attachable to a door adjacent a door hole,

wherein the sleeve includes a tapered inner surface,

a handle shaft,

wherein the handle shaft comprises an axis,

wherein the handle shaft includes a tapered outer surface,

a handle lever.

wherein the <u>tapered</u> inner surface is operative to engage the <u>tapered</u> outer surface to prevent removal of the handle shaft through the door hole in a <u>an axial</u> direction away from the handle lever,

wherein the tapered outer surface when in engagement with the tapered inner surface narrows in the axial direction away from the handle lever.

wherein the sleeve tapered inner surface is operative to be substantially located on an opposite side of the door from the handle lever when in engagement with the handle shaft tapered outer surface.

wherein the sleeve includes at least one non tapered inner surface section extending in the axial direction,

wherein the handle shaft includes at least one non tapered cuter surface section extending in the axial direction.

wherein the at least one handle shaft section is operative to engage the at least one sleeve section on an opposite side of the door from the handle lever to align the handle shaft relative to the door.

34. (currently amended) The apparatus according to claim 31 wherein the handle shaft comprises an axis;

wherein the sleeve includes non tapered inner surface sections extending in the axial